

POWERFUL PERFORMANCE FOR THE LONG RUN

Fujitsu Services introduces D25 15" LCD



Fujitsu Services D25 (Digital and analogue) LCD with optional resistive touch is a USB device designed for use on all variants of the TeamPoS 3000 PoS Terminals & TP-X.

The **D25 15" LCD** flat panel is an ergonomic and space saving solution which is style compatible with the TeamPoS 3000.

The LCD supports two (2) video interfaces. VGA support is provided to connect to existing legacy motherboards. The DVI interface is available for newer industry standard motherboards. The LCD stand provided can be either stacked or used in a dispersed configuration. Additionally the LCD can be mounted on a pole such as Team Pole.

MSR and keypad/MSR 123 are available as added options.

The keypad provides the ability of inputting key-entry data. The colour LCD provides presentation of text, graphics, and user guidance, while ease in data input is provided through the touch screen, keypad and MSR.

The flat panel display unit is a flexible system that provides up to four different interface. These interfaces are:

- Full screen graphical user interface (GUI)
- Touch screen interface for point and touch capabilities
- 32-key Keypad/Magnetic Stripe Reader (MSR)
- Magnetic Stripe Reader (MSR) only interface.



TeamPoS 3000 Peripherals
Dependable PoS from Fujitsu Services

D25 15" LCD – Key Features

LCD with Touch capabilities The D25 15" LCD is available with both resistive and infrared touch. The D25 LCD has both DVI and VGA interfaces and automatically detects which interface is attached. The colour LCD provides presentation of text, graphics and user guidance, while ease in data input is provided through the touch screens, keypad and MSR. Speakers are standard while power is provided through a powered USB cable connection.

Keypad and MSR input The D25 15" LCD has the option of adding onto the side of the unit a 32 key keypad and/or MSR (Magnetic Stripe Reader). The keypad and MSR modules (which are fully programmable) provide an integrated method of data entry within an application. A 4-position keylock (part of the 32 key keypad) is provided and the positions are Operator (OP), Manager (MGR), Auxiliary (AUX) and Lock. The 3 track MSR (Tracks 1,2,3) option provides the capability to read magnetic card data from all 3 tracks.

Mounting options

Stacked The D25 Stacked Stand: This option includes an integrated stand that can be fastened to the controller with standard brackets and screws. This stand includes the option to integrate the VF60 Customer Display by simple removal of a circular disc that exposes an area on the back of the stand to screw in the VF60 customer display. The stacked stand includes brackets to secure on top of the control unit.

Dispersed Stand The dispersed stand can be used in environments where the display is not stacked on the TeamPoS 3000 control unit.


Standard VESA Mount The D25 LCDs include standard VESA mounting holes for use with standard VESA mounts. A different back cover needs to be ordered in order to support the customer-supplied VESA pole.

Team Pole In addition to the above mounting options Fujitsu Services can provide an all purposes pole solution called TeamPole which is a new polekit designed to meet the demands of today's retailer at an affordable price. Ergonomically designed the Team Pole can be used in almost all retail environments to support either 12" or 15" displays (supporting either VESA 75 or 100 mounts).

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com

D25 15" LCD Technical Specifications



| | |
|--------------------|--|
| LCD | TFT, 15 inch panel backlight diagonal |
| Colours (Plastics) | Black & White |
| Resolution | SVGA, 1024 x 768 pixels |
| Interface | DVI or VGA |
| Audio Speaker | Standard (PC Speaker) with 1.5 watt max per channel audio output |
| Operator Controls | Brightness and speaker volume |
| Dimensions (mm) | 365 (14.4in.)(W) x 60 (2.4in.)(D) x 296 (11.6 in.) (H) |
| Options | Integrated /Distributed stand |
| | MSR |
| | Keypad |
| Touch Panel | Resistive or Infra Red with USB interface |
| VESA Mount | Fully compliant |
| Indicators | Signal/Power LED |
| Brightness | 250 cd/m2 Min (without touch) 200 cd/m2 Min (with touch) |
| Contrast Ratio | 250:1 Min |
| Colours | 260,000 |
| Weight | 670g ± 50g (1.5 lbs) |



TeamPoS 3000 Peripherals
Dependable PoS from Fujitsu Services

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com