


**NOTES:**

**ELECRICAL:**

- (1). 100% CONTINUITY (OPEN, SHORT, MISSWIRE) ;
- (2). INSULATION RESISTANCE:300V, 5MΩ MIN;
- (3). CONDUCTIVE RESISTANCE: :5Ω MAX;
- (4). 100% HDTV-DVD TEST:4K\*2K@60HZ;
- (5). WIRE SURFACE PRINTING(White):/

NO.	Part name	Specifications describe	Dosage	UNIT
⑧	PE BAG	PE BAG:W155*L175*T0.05mm	1	PCS
⑦	MINI TIE	TIE, METAL MATERIAL INSIDE, BLACK OUTSIDE	1	PCS
⑥	O-ring	O-ring GREEN COLOR	2	PCS
⑤	OUTER MOLD	87A TPU, COLOR FOR BLACK	2	PCS
④	INNER MOLD	LDPE, COLOR FOR WHITIE	2	PCS
③	CONNECTOR 2	HDMI 19P/FEMALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+PCBA(IC CS5265)	1	PCS
②	CONNECTOR 1	USB TYPE C MALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+10uF	1	PCS
①	TYPE C CABLE	(1/0.20BC*1P+AL)*4C+1/0.20BC*1P+1/0.20BC*4C+41/0.08BC*2C+AL, BLACK TPU JACKET, OD:4.8±0.2mm	1	PCS

Pack Draw:



Approved	Reviewer	Drawing	Drawing No.	TYO***		MPN: MC-USBC HDMI-A	
Emil Olsen	Franck	Xu.gy	ITEM No.	TYPE C/M-HDMI A/F-***M(GOLD)			
			Customer Name				
			Unit	mm	Tolerance	X. ±1.00	
			Graphic			X.X ±0.50	