

POWERFUL PERFORMANCE FOR THE LONG RUN

Fujitsu Services introduces D22 12.1" LCD



Fujitsu Services D22 (Digital and analogue) LCD with optional resistive touch is a USB device designed for use on all variants of the TeamPoS 3000 PoS Terminals & TP-X.

The **D22 12.1" LCD** is an ergonomic and space saving solution. The flat panel display unit is a flexible system that provides up to four different interfaces. These interfaces are:

- Full screen graphical user interface (GUI)
- Touch screen interface for point and touch capabilities
- 32-key Keypad/Magnetic Stripe Reader (MSR)
- Magnetic Stripe Reader (MSR) only interface.

Speakers are standard and require an additional audio cable.



TeamPoS 3000 Peripherals
Dependable PoS from Fujitsu Services

D22 12.1" LCD – Key Features

LCD with Touch capabilities The D22 12.1" LCD has resistive touch as an option. The colour LCD provides presentation of text, graphics and user guidance, while ease in data input is provided through the touch screens, keypad and MSR.

Keypad and MSR input The D22 12.1" LCD has the option of adding onto the side of the unit a 32 key keypad and/or MSR (Magnetic Stripe Reader). The keypad and MSR modules (which are fully programmable) provide an integrated method of data entry within an application. A 4-position keylock (part of the 32 key keypad) is provided and the positions are Operator (OP), Manager (MGR), Auxiliary (AUX) and Lock. The 3 track MSR (Tracks 1,2,3) option provides the capability to read magnetic card data from all 3 tracks.

Mounting options There are several options for mounting the D22 12.1" LCD:

Stacked The D22 Stacked Stand: This option includes an integrated stand that can be fastened to the controller with standard brackets and screws. This stand includes the option to integrate the VF60 Customer Display by simple removal of a circular disc that exposes an area on the back of the stand to screw in the VF60 customer display. The stacked stand includes brackets to secure on top of the control unit.

Dispersed Stand The dispersed stand can be used in environments where the display is not stacked on the TeamPoS 3000 control unit.

Standard VESA Mount The D22 LCDs include standard VESA mounting holes for use with standard VESA mounts. A different back cover needs to be ordered in order to support the customer-supplied VESA pole.

Team Pole In addition to the above mounting options Fujitsu Services can provide an all purposes pole solution called TeamPole. Team Pole is a new polekit designed to meet the demands of today's retailer at an affordable price. Ergonomically designed the Team Pole can be used in almost all retail environments to support either 12" or 15" displays (supporting either VESA 75 or 100 mounts). For more information on Team Pole go to the RPG Portal.

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com

D22 12.1" LCD Technical Specifications



LCD	TFT, 12.1 inch panel backlight diagonal
Colours (Plastics)	Black & White
Resolution	SVGA, 800 x 600 pixels, max
Interface	DVI or VGA
Audio Speaker	Standard (PC Speaker) with 1.5 watt max per channel audio output
Operator Controls	Brightness and speaker volume
Dimensions (mm)	303 (12in.)(W) x 54 (2.1in.)(D) x 254 (10 in.)(H)
Options	Integrated /Distributed stand
	MSR
	Keypad
Touch Panel	Resistive with USB interface
VESA Mount	Fully compliant
Indicators	Signal/Power LED
Brightness	250 cd/m2 Min (without touch) 200 cd/m2 Min (with touch)
Contrast Ratio	250:1 Min
Colours	260,000
Weight	670g ± 50g (1.5 lbs)

TeamPoS 3000 Peripherals
Dependable PoS from Fujitsu Services

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com

